

Juice Bar® Mini Bar Double

Product Specifications



Features:

- Two Level 2 chargers
- Four Level 1 chargers
- ETL Listed
- IP Rating: NEMA 3R
- Charges all makes and models
- Built-in point of sale
- Upgradable & future-tech ready
- Compatible with all EV networks
- Customizable look and design
- Highly durable enclosure
- Flexible installation options
- Highly visible LED illumination

Additional Options & Attachments:

- Cord management system
- Pedestal/wall/pole mounts
- Tough connect charging plugs
- Digital control & accessibility
- Cellular & network access
- User apps & online data access
- Revenue management software

AC Input from Utility - Level 2

Voltage 208/240 VAC
Breaker Rating 40A (requires 2)

AC Output to Vehicle - Level 2

Voltage 208/240 VAC
32A (7.7kW max) each side

AC Input - Level 1

Voltage 120 VAC
Breaker Rating 20A - (requires 2)

Operating Temperature

-30°C to 55°C (-22°F to 122°F)

Communications

Ethernet or Cellular

Connector - Level 2

SAE compliant J1772 Connector

Dimensions

Height: 36.5" (60" with pedestal option)
Width: 16" (36" with connectors on each side)
Depth: 12 3/8"

Cord Length

23 feet

Unit Material

Unit: Powder Coated Aluminum
Pedestal: Powder Coated Steel

Limited Product Warranty Available



BMW Group
DesignworksUSA

