

# JB3.0 40A

## LEVEL 2 COMMERCIAL CHARGING



sales@sparkev.ca  
(416) 931-7944  
sparkev.ca

### MINIBAR - TECHNICAL SPECIFICATION

<b>Certifications</b>	<b>IP Rating</b>
TUV Rheinland Certified Compliance (pending)	UL991, 2231-2, 2594 & NEMA 3R
<b>AC Input from Utility - Level 2</b>	<b>Operating Temperature</b>
Voltage 208/240 VAC Breaker Rating 50A Single: 3 wire (L1, L2 & G) Double: 5 wire (L1, L1, L2, L2, & G)	-30°C to 55°C (-22°F to 122°F)
<b>AC Output to Vehicle - Level 2</b>	<b>Communications</b>
Voltage 240 VAC 40A (9.6 kW max) each side	Ethernet or Cellular
<b>Protocol</b>	
OCPP 1.6J Multi-Network	
<b>Dimensions</b>	
<b>Height:</b> 36.5" (unit) / 72" (w/pedestal)	
<b>Width:</b> 16" (unit) / 36" (w/connectors plugged in at each side)	
<b>Depth:</b> 12"	
<b>Connector - Level 2</b>	<b>Cord Length</b>
SAE J1772 Connector	18'
<b>Unit Material</b>	<b>Pedestal Material</b>
Powder Coated Aluminum	Powder Coated Steel

<b>Customization Options:</b>	<b>User Interface</b>
<ul style="list-style-type: none"> <li>• Branded LED Backlit Logo</li> <li>• Branded Door Skin</li> <li>• Branded Door Decal</li> <li>• Powder Coat Colour Choice</li> <li>• GFCI Outlets</li> <li>• E-Bike/Scooter Lock Points</li> </ul>	<ul style="list-style-type: none"> <li>• Mobile Application</li> <li>• QR Code Enabled</li> <li>• RFID Card Reader</li> <li>• LED Indicators</li> </ul>

