

JB3.0 80A

LEVEL 2 COMMERCIAL CHARGING



sales@sparkev.ca
(416) 931-7944
sparkev.ca

MINIBAR - TECHNICAL SPECIFICATION

Certifications	IP Rating
TUV Rheinland Certified Compliance (pending)	UL991, 2231-2, 2594 & NEMA 3R
AC Input from Utility - Level 2	Operating Temperature
Voltage 208/240 VAC	-30°C to 55°C (-22°F to 122°F)
Breaker Rating 100A	
Single: 3 wire (L1, L2 & G)	
Double: 5 wire (L1, L1, L2, L2, & G)	
AC Output to Vehicle - Level 2	Communications
Voltage 240 VAC	Ethernet or Cellular
80A (19.2kW max) each side	
Protocol	
OCPP 1.6J Multi-Network	
Dimensions	
Height: 36.5" (unit) / 72" (w/pedestal)	
Width: 16" (unit) / 36" (w/connectors plugged in at each side)	
Depth: 12"	
Connector - Level 2	Cord Length
SAE J1772 Connector	18'
Unit Material	Pedestal Material
Powder Coated Aluminum	Powder Coated Steel

Customization Options:

- Branded LED Backlit Logo
- Branded Door Skin
- Branded Door Decal
- Powder Coat Colour Choice
- GFCI Outlets
- E-Bike/Scooter Lock Points

User Interface

- Mobile Application
- QR Code Enabled
- RFID Card Reader
- LED Indicators