


Gen 3 480 SERIES: 48A LEVEL 2

MODEL #	DESCRIPTION
JB3.0-481	Single Connector Charger
JB3.0-482	Dual Connector Charger
CERTIFICATIONS	
TUV Rheinland	
UL 2231-1, UL 2231-2, UL 2594	
AC INPUT	
Voltage: 208/240 VAC	
Breaker: Rating 60A	
Single Connector: 3 Wire (L1, L2 & G)	
Double Connector: 5 Wire (L1, L1, L2, L2 & G)	
(or)	
Voltage: 208/240 VAC	
Breaker: Rating 120A	
Double Connector: 3 Wire (L1, L2 & G)	
AC OUTPUT PER CONNECTOR	
11.5 kW at 240VAC	
10kW at 208VAC	
OPERATING TEMPERATURE	
- 25° C to +50° C	
- 13° F to +122° F	
COMMUNICATIONS	
Cellular	
PROTOCOL	
OCPP 1.6J	
DIMENSIONS	
71.25" Total Height with Pedestal	
36.5" Total Height w/out Pedestal	
16" Width Without Connectors	
12" Depth	
CORD LENGTH	
18 feet (standard)	
CONNECTORS	
SAE J1772 Type 1	
ENCLOSURE	
Type 3R Aluminum	
OPTIONS	
Wall Bracket	
Pedestal Mount	
Branded Door Graphics	
GFCI Outlet & Bike Lock Loop	
USER INTERFACE	
LED Indicators	
RFID Card Reader	



sales@sparkev.ca
(416) 931-7944
sparkev.ca

